

# FT-400 FT-800LD



MODEL	SITTEN FT-400	SITTEN FT-800LD
Part Number	POS2044	POS2114
Capacity	400VA/240W	800VA/480W
<b>INPUT</b>		
Phase	Single + GND	Single + GND
Voltage	110/115/120VAC or 220/230/240VAC	220/230/240VAC
Voltage break	165V-275V/82V-138V	165V-175V/82V-138V
Frequency	50Hz/60Hz +/- 10% (Auto Sensing)	50Hz/60Hz +/- 10% (Auto Sensing)
<b>OUTPUT</b>		
Voltage break	220V/230V/240V/110V/120VAC +/- 10%	220/230/240VAC +/- 10%
Wave type	Sine wave	Sine wave
Frequency	50Hz/60Hz +/- 1% (battery mode)	50Hz/60Hz +/- 1% (battery mode)
Transfer time	≤6ms	≤6ms
<b>BATTERY</b>		
Type	Sealed Lead-acid	Sealed Lead-acid
Charging time	90% of the capacity in 5 hours	90% of the capacity in 5 hours
Autonomy	8-12 min, depending on the equipment	20-35 min, depending on the equipment
Security protection	Over Charge & Over Discharge	Over Charge & Over Discharge
<b>FUNCTIONS</b>		
General	Incorporated AVR   Cold start DC   Audible and visual alarms   Compatible with generators   Intelligent management of the battery   Energized line with wide entry   Automatic charging in offline mode   Continuous surge suppression and noise filter   Short-circuit protection and low voltage battery	
Socket	3 Schuko w/ power supply	3 Schuko w/ power supply
Display	Não	Yes (autonomy, consumption and voltage)
<b>ENVIRONMENT</b>		
Running temperature	0-40°C	0-40°C
Humidity	0-90% (without compensation)	0-90% (without compensation)
Noise	<40dB (1 meter)	<40dB (1 meter)
<b>GENERAL</b>		
Dimensions	305x98x170 (DxWxH)	305x98x170mm (DxWxH)
Weight	4Kg	5Kg