

# AIO 1088S



| MODEL                          |  | SITTEN AIO 1088S  |
|--------------------------------|--|---|
| Part Number                    |  | POS1144   |
| EAN                            |  | -   |
| MAIN SYSTEM                    |  |   |
| CPU                            |  | Intel® Celeron® J1900   |
| Memory                         |  | 2Gb DDR3  |
| Storage                        |  | 32GB SSD SATA   |
| OS Compatibility               |  | Windows 7, Windows 8.1  |
| INTEGRATED DEVICES AND SENSORS |  |   |
| Graphic card                   |  | Intel Graphics Media  |
| Audio card                     |  | Accelerator3150 (256MB / Intel) - RTL ALC662INTEL 82801G (ICH7) High Definition Audio |
| Printer                        |  | Seiko 80mm thermal printer  |
| Screen or client display       |  | Yes- VFD 2 lines  |
| Magnetic stripe reader (MSR)   |  | Optional  |
| COMMUNICATION                  |  |   |
| Network card                   |  | 10/100/1000Mbps   |
| WiFi                           |  | No (Optional)   |
| PORTS AND CONNECTIONS          |  |   |
| Graphics                       |  | 1 x VGA   |
| USB                            |  | 4 x USB 2.0   |
| Network                        |  | 1 x RJ45  |
| Serial                         |  | 3 x RS232   |
| Drawer                         |  | 1 x RJ11  |
| SCREEN AND GRAPHICS            |  |   |
| Screen                         |  | 12" TFT LCD   |
| Resolution                     |  | 1024x768  |
| Touch Screen                   |  | 85° adjustable  |
| Viewing angle                  |  | 5-wire resistive 20 000 000 touches   |
| Brightness/Contrast            |  | 250 cd/m <sup>2</sup>   |
| OTHER                          |  |   |
| Dimensions (WxHxD)             |  | 350 x 225 x 375 mm (POS)   400x310x440 mm (box)                                       |
| Weight                         |  | 5,860Kg (POS)   7,685Kg (withbox)   |
| Power supply                   |  | Adaptor 100-240V/ 3.5A 47~63Hz  |
| Temperature                    |  | Running: 0°C~40°C   Storage: -40°C~50°C   |
| Humidity                       |  | 38~80%  |
| Certifications                 |  | CE, FCC, KC   |